

ILS or LOC RWY 3

LOC/DME I-AEZ **APCH CRS** **Rwy Idg** **TDZE** **ELEV**

108.5 Chan 22	029°	8637	685	690
-------------------------	-------------	-------------	------------	------------

[USA] **WHEELER-SACK AAF** (KGTB)

DME or RADAR required. RADAR required for procedure entry.

ALSF-1 MISSED APPROACH: Climb to 1200, then climbing left turn to 5000 direct ART VORTAC and hold. Continue climb-in-hold to 5000.

ATIS	APP CON	TOWER	GND CON	CLNC DEL	ASR/PAR
119.525	124.875 307.125	118.75 290.25	123.65 229.8	123.65	

*** When ALS inop, increase CAT AB vis to 1 mile;
CAT C vis to 1½ miles; CAT D vis to 1¼ miles;
CAT E vis to 1½ miles.
*** Circling NA E of Rwy 21 and 33.
Circling NA for CAT BCD to Rwy 8.
Circling NA for CAT E to Rwy 8-26 and 15-33.

ALTERNATE MISSED APPROACH: When directed by ATC, climb to 1200, then climbing left turn to 3000 via hdg 340° within 10 NM (RADAR required).

CATEGORY	A	B	C	D	E
S-ILS 3 *	957-½ 272 (300-½)				
S-LOC 3 **	1560-½ 875 (900-½)	1560-¾ 875 (900-¾)	1560-2 875 (900-2)	1560-2¼ 875 (900-2¼)	1560-2½ 875 (900-2½)
CIRCLING ****	1560-1¼ 870 (900-1¼) 1560-2½ 870 (900-2½) 1560-2¾ 870 (900-2¾) 1640-3 950 (1000-3)				

DME MINIMUMS

S-LOC 3 ***	1080-½ 395 (400-½)	1080-¾ 395 (400-¾)	1080-1 395 (400-1)
CIRCLING ****	1200-1 510 (600-1)	1220-1½ 530 (600-1½)	1380-2¼ 690 (700-2¼)

Min:Sec 6:54 4:36 3:27 2:46 2:11