

WAAS

CH 93835

W22A

APP CRS

220°

Rwy Idg

5002

TDZE

182

Apt Elev

182

RNAV (GPS) RWY 22

DEXTER B FLORENCE MEML FLD (ADF')


▼

NA

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hot Springs altimeter setting and increase all MDAs 120 feet, and increase LP and LNAV Cat C visibility ⅔ SM and Circling Cat C visibility ½ mile. Night landing: Rwy 22 NA. Helicopter visibility reduction below 1 NM NA.

MISSED APPROACH: Climb to 2000 direct CUBUG and hold.

AWOS-3PT 118.175	MEMPHIS CENTER 128.475 377.15	UNICOM 122.7 (CTAF) 0
---------------------	----------------------------------	--------------------------



2000

CUBUG

Visual Segment - Obstacles.

ITVOW 1.7 NM to RW22

ZULSO

COVNO

4 NM Holding Pattern

2100

040°

220°

760

2000

1.7

3.9 NM

5 NM

CATEGORY	A	B	C	D
LP MDA	600-1	418 (500-1)	600-1⅓ 418 (500-1⅓)	NA
LNAV MDA	680-1	498 (500-1)	680-1⅓ 498 (500-1⅓)	NA
CIRCLING	760-1 578 (600-1)	800-1 618 (700-1)	1040-2½ 858 (900-2½)	NA

