

WAAS CH 45717 W20A	APP CRS 202°	Rwy Idg TDZE Apt Elev	6450 874 874
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20

MCMINN COUNTY (MMI)

RNP APCH - GPS.

▼


⚠

Circling Rwy 2 NA at night. Baro-VNAV and VDP NA when using Mc Ghee Tyson altimeter setting.

Rwy 20 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Mc Ghee Tyson altimeter setting: increase LPV DA to 1275 feet and visibility all Cats $\frac{1}{8}$ SM; increase LNAV/VNAV DA to 1819 feet and visibility all Cats $1\frac{1}{2}$ SM; increase all MDAs 120 feet and LNAV visibility Cat C and D $\frac{1}{2}$ SM, and Circling visibility Cat A and C $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 4100 direct ZAGUG and hold.

AWOS-3 125.425	KNOXVILLE APP CON 123.9 353.6	UNICOM 122.8 (CTAF)
--------------------------	---	-------------------------------



ELEV 874	TDZE 874
-----------------	-----------------

4100 ZAGUG ↑				
RWY 20 NONOC 3.1 NM to RWY 20 GIMFY 2800 HUVEP 4 NM Holding Pattern 6000 3100 GP 3.00° TCH 40 2.2 0.9 2.7 6.1 NM				
CATEGORY	A	B	C	D
LPV DA	1174-1		300 (300-1)	
LNAV/VNAV DA	1718-2 $\frac{1}{2}$		844 (900-2 $\frac{1}{2}$)	
LNAV MDA	1620-1 746 (800-1)	1620-1 $\frac{1}{4}$ 746 (800-1 $\frac{1}{4}$)	1620-2	746 (800-2)
CIRCLING	1620-1 746 (800-1)	1620-1 $\frac{1}{4}$ 746 (800-1 $\frac{1}{4}$)	1620-2 $\frac{1}{4}$ 746 (800-2 $\frac{1}{4}$)	1820-3 946 (1000-3)