

WAAS CH 93735 W02A	APP CRS 018°	Rwy Idg TDZE 262 Apt Elev 262
--	------------------------	---

RNAV (GPS) RWY 2

KENNETT MEML (TKX)

⚠

NA

Circling to Rwy 18/36 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Circling NA west of Rwy 2 and 18. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Blytheville altimeter setting and increase all DA 47 feet and all MDA 60 feet; increase LNAV/VNAV visibility all Cats and LNAV Cats C/D visibility ½ mile; increase Circling Cat D visibility ¼ mile. Helicopter visibility reduction below 1 SM NA. Rwy 2 Straight-in and Circling minimums NA at night.

MISSED APPROACH:

Climb to 2500 direct OGVIE and hold.

AWOS-3PT 119.05	MEMPHIS CENTER 120.075 289.4	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------

⚠ 862

30 NM to COSAD

2500

108°

COSAD

288°

108°

COSAD

288°

30 NM to COSAD (NoPT)

2500

405 ⚠

670 ⚠

354 ±

⚠ RW02

ZISGO

2 NM to RW02

(FAF) HESLU

1900

018° (6.1)

(IF/IAF) COSAD

4 NM

198°

018°

MISSED APCH FIX

4 NM

198°

198°

OGVIE

ELEV 262

TDZE 262

4 NM Holding Pattern

2500

198°

018°

COSAD

HESLU

1900

ZISGO

2 NM to RW02

RW02

2500

OGVIE

*LNAV only.

GP 3.00°

TCH 40

6.1 NM

3 NM

2 NM

CATEGORY	A	B	C	D
LPV DA		512-1	250 (300-1)	
LNAV/VNAV DA		538-1	276 (300-1)	
LNAV MDA		620-1	358 (400-1)	
CIRCLING	660-1 398 (400-1)	720-1 458 (500-1)	720-1½ 458 (500-1½)	900-2 638 (700-2)

81

3012 X 75

20

36

5000 X 75

018° to RW02

REIL Rwy 2 and 20

MIRL Rwy 2-20 and 18-36

KENNETT, MISSOURI

Amdt 1A 28APR16

36°14'N-90°02'W

KENNETT MEML (TKX)

RNAV (GPS) RWY 2