

APP CRS  
**213°**

Rwy Idg  
TDZE  
**763**

Apt Elev  
**763**

**RNAV (GPS) RWY 22**

HURON COUNTY MEML (BAX)


RNP APCH.

▼

When local altimeter setting not received, use MBS Intl altimeter setting and increase all MDA 140 feet; increase LNAV Cat C visibility ½ SM. Procedure NA at night. Rwy 22 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 3000 direct CASKU and hold.

|                        |                                          |                                   |
|------------------------|------------------------------------------|-----------------------------------|
| AWOS-3<br><b>118.6</b> | CLEVELAND CENTER<br><b>127.7 290.425</b> | UNICOM<br><b>123.075 (CTAF) 0</b> |
|------------------------|------------------------------------------|-----------------------------------|



ELEV 763

TDZE 763

213°

3495-775

5000-775

35

3000

CASKU

Visual Segment - Obstacles.

IDICE

4 NM Holding Pattern

RW22

KEVEC 2 NM to RW22

JANIK

2500

1440

2 NM

3.3 NM

6.2 NM

| CATEGORY | A      | B           | C | D  |
|----------|--------|-------------|---|----|
| LNAV MDA | 1140-1 | 377 (400-1) |   | NA |