

WAAS CH 42505 W31A	APP CRS 314°	Rwy Idg 6500 TDZE 487 Apt Elev 501
--	------------------------	---

RNAV (GPS) RWY 31


LANCASTER RGNL (LNC)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. Baro-VNAV NA when using Dallas Exec altimeter setting. When local altimeter setting not received, use Dallas Exec altimeter setting and increase LPV DA to 732 feet; increase LNAV/VNAV DA to 970 feet and visibility all Cats ¼ SM; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cats C/D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct DOCAV and right turn on track 053° to WARER then climb to 3000 on track 053° to SOLD0 and hold.

AWOS-3PT 118.975	LONE STAR APP CON 125.2 343.65	GCO 121.725	UNICOM 122.7 (CTAF) 0
----------------------------	--	-----------------------	---------------------------------



ELEV 501	TDZE 487	2000 DOCAV WARER 3000 SOLD0 VIYUN
* LNAV only		
OTAZY 1.5 NM to RW31		
RW31		
JUTON 1800		
VIYUN 2700		
GP 3.00° TCH 50		
CATEGORY	A	B
LPV DA	687-¾	200 (200-¾)
LNAV/VNAV DA	925-1½	438 (500-1½)
LNAV MDA	880-1	393 (400-1)
CIRCLING	980-1 479 (500-1)	1020-1 519 (600-1)