

WAAS
CH **77809**
W16A

APP CRS
163°

Rwy Idg **4301**
TDZE **1803**
Apt Elev **1803**

RNAV (GPS) RWY 16
AURORA MUNI/AL POTTER FLD (AUH)

⚠

Baro-VNAV NA when using Grand Island altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Grand Island altimeter setting and increase all DA 41 feet and all MDA 60 feet and all LPV all Cats visibility ¼ mile. VDP NA when using Grand Island altimeter setting.

MISSED APPROACH:

Climb to 3400 direct EBWIX and hold.

AWOS-3 121.225	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

Procedure NA for arrival on GRI VOR/DME airway radials 077 CW 108.

MSA RWY 16 25 NM
4100

4 NM Holding Pattern

3400 ← 343°

163° →

3400

GP 3.00°
TCH 40

CEGIT

FOBDO

CAKAY 2 NM to RW16

RW16

3400

3400

*2480

*1 NM to RW16

EBWIX

*LNAV only

CATEGORY	A	B	C	D
LPV DA	2102-1	299 (300-1)		NA
LNAV/VNAV DA	2133-1¼	330 (400-1¼)		NA
LNAV MDA	2160-1	357 (400-1)		NA
CIRCLING	2300-1 497 (500-1)	2340-1 537 (600-1)		NA

MIRL Rwy 16-34 0

AURORA, NEBRASKA
Amdt 1B 13AUG20

40°54'N-98°00'W

AURORA MUNI/AL POTTER FLD (AUH)
RNAV (GPS) RWY 16