

Baro-VNAV NA. Circling Rwy 13, 31 NA at night. DME/DME RNP-0.3 NA. Use Lubbock altimeter setting. When not received, use Seminole altimeter setting and increase LPV DA to 3600; increase LNAV/VNAV DA to 3600; and increase all MDA 20 feet.

MISSED APPROACH: Climb to 5200 direct LEBDE and hold.

LBB ASOS 125.3 270.275	LUBBOCK APP CON 119.2 351.8	UNICOM 122.8 (CTAF) 0
---------------------------	--------------------------------	--------------------------

MISSED APCH FIX
5 NM
LEBDE

30 NM to WOGFE

15 NM to WOGFE

5000

5300

107°

287°

WOGFE

30 NM to WOGFE

15 NM to WOGFE

5000

5300

107°

287°

WOGFE

30 NM to WOGFE (NoPT)

15 NM to WOGFE

5000

5300

107°

287°

WOGFE

3739

3533

3840

3301±

RW02

SLOBS 2.4 NM to RW02

(FAF) FATYO

4900

017°

197°

(IF/IAF) WOGFE

5 NM

5 NM Holding Pattern

WOGFE

5000

197°

017°

017°

FATYO

4900

SLOBS 2.4 NM TO RW02

RW02

5200

LEBDE

*LNAV only.

GP 3.00°

TCH 43

6 NM

2.6 NM

2.4 NM

4060

ELEV 3265

TDZE 3256

20

15

10

5

0

2

1

27.65 X 75

5218 X 75

0.4% UP

017°

MIRL Rwy 2-20 0

CATEGORY	A	B	C	D
LPV DA		3589-1	333 (400-1)	
LNAV/VNAV DA		3589-1	333 (400-1)	
LNAV MDA	3640-1	384 (400-1)	3640-1 1/8	384 (400-1 1/8)
CIRCLING	3760-1 495 (500-1)	3920-1 655 (700-1)	3980-2 715 (800-2)	4100-2 3/4 835 (900-2 3/4)

BROWNFIELD, TEXAS

33°10'N-102°12'W

TERRY COUNTY (BFE)

Amtd 1 29MAR18

RNAV (GPS) RWY 2