

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

MISSED APPROACH:
Climb to 3000 direct
URACE and hold.

AWOS-3 133.975	NASHVILLE APP CON 118.4 360.7	GCO 135.075	UNICOM 123.075 (CTAF)
-------------------	----------------------------------	----------------	--------------------------

ELEV 614

TDZE 609

MIRL Rwy 18-36
REIL Rws 18 and 36

MISSED APCH FIX

URACE

004°

184°

4 NM

3000

URACE

VGSI and descent angles not coincident
(VGSI Angle 3.00/TCH 20).

4 NM

Holding Pattern

UZFUR

004°

184°

3000

GP 3.00°

TCH 40

AHINO

3.1 NM to RW18

ESKOC

2500

*1.4 NM to RW18

*1620

*2500

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	859-3/4	250 (300-3/4)		NA
LNAV/VNAV DA	898-7/8	289 (300-7/8)		NA
LNAV MDA	1080-1	471 (500-1)	1080-1 3/8 471 (500-1 3/8)	NA
CIRCLING	1080-1	466 (500-1)	1280-1 3/4 666 (700-1 3/4)	NA

MURFREESBORO, TENNESSEE

MURFREESBORO MUNI (MBT)

Amdt 2 29MAR18

35°53'N-86°23'W

RNAV (GPS) RWY 18