


WAAS CH 63120 W10A	APP CRS 094°	Rwy Idg TDZE Apt Elev 5200 840 840
--	------------------------	--

RNAV (GPS) RWY 10

WAUPACA MUNI (PCZ)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV ▲ NA below -16°C or above 54°C.		MISSED APPROACH: Climb to 2800 direct WVEGA and hold.
AWOS-3 118.625	MINNEAPOLIS CENTER 124.4 317.7	UNICOM 122.8 (CTAF) 0



4 NM

Holding Pattern

BRUNR

6000

2800

← 274°

→ 094°

GP 3.00°

TCH 40

CUTTS

2700

094°

2700

*1540

*1.6 NM to RW10

RW10

2800

WWEGA

↑

✦

*LNAV only.

7.7 NM

3.6 NM

0.5

1.6 NM

094°

13

3899 X 75

5200 X 100

228

31

0.6% UP

0.7% UP

REIL Rwy 10 and 28

MIRL Rwy 10-28 and 13-31

CATEGORY	A	B	C	D
LPV DA	1090-¾		250 (300-¾)	
LNAV/VNAV DA	1384-1⅝		544 (600-1%)	
LNAV MDA	1380-1	540 (600-1)	1380-1½	540 (600-1½)
CIRCLING	1380-1 540 (600-1)	1420-1 580 (600-1)	1420-1½ 580 (600-1½)	1500-2 660 (700-2)