

WAAS
CH **70522**
W21A

APP CRS
213°

Rwy Idg
TDZE **718**
Apt Elev **718**

5001
718
718

RNAV (GPS) RWY 21
MARK ANTON (2A0)

Baro-VNAV NA when using Chattanooga altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 39°C (102°F). DME/DME RNP-0.3 NA. When VGSI inop, Straight-in/Circling Rwy 21 NA at night. When local altimeter setting not received, use Chattanooga altimeter setting: increase LPV DA to 1085 feet, LNAV/VNAV DA to 1249 feet, and visibility LPV and LNAV/VNAV all Cats ¼ SM; increase all MDA 80 feet and visibility LNAV Cat C/D ¼ SM and Circling Cat C ½ SM. Rwy 21 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:
Climb to 3900 direct CETPO and hold, continue climb-in-hold to 3900.

AWOS-3 135.075	CHATTANOOGA APP CON ★ 125.1 379.1	UNICOM 123.0 (CTAF)
--------------------------	---	-------------------------------

ELEV 718	TDZE 718
213°	21
3900	CETPO
*LNAV only.	HISMU 2.3 NM to RW21
RW21	*1480
2.3 NM	2.9 NM
2400	2400
WATZ	4 NM Holding Pattern
033°	3900
GP 3.00°	TCH 31
CATEGORY	A B C D
LPV DA	1010-1 292 (300-1)
*LNAV/VNAV DA	1174-1½ 456 (500-1½)
LNAV MDA	1140-1 422 (500-1)
	1140-1¼ 422 (500-1¼)
CIRCLING	1380-1 662 (700-1) 1420-1 702 (800-1) 1520-2¼ 802 (900-2¼) 1620-3 902 (1000-3)

DAYTON, TENNESSEE

MARK ANTON (2A0)

Amdt 1B 02DEC21

35°29'N-84°56'W

RNAV (GPS) RWY 21