

|                                        |                        |                                                                 |
|----------------------------------------|------------------------|-----------------------------------------------------------------|
| WAAS<br>CH <b>61216</b><br><b>W20A</b> | APP CRS<br><b>200°</b> | Rwy Idg <b>6100</b><br>TDZE <b>3786</b><br>Apt Elev <b>3788</b> |
|----------------------------------------|------------------------|-----------------------------------------------------------------|

RNAV (GPS) RWY 20  
HEREFORD MUNI (HRX)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 41°C. When local altimeter setting not received, use AMA altimeter setting: increase LPV DA to 4098 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 4232 feet and all visibilities ¼ SM; increase all MDAs 120 feet and LNAV visibility Cats C and D ½ SM, increase Circling visibility Cat C ½ SM and Cat D ¼ SM. Circling NA to Rwy 14 and 32. Baro-VNAV and VDP NA when using AMA altimeter setting.

MISSED APPROACH:  
Climb to 6000 direct  
LEMGE and hold.

|                         |                                          |                                 |
|-------------------------|------------------------------------------|---------------------------------|
| AWOS-3<br><b>118.05</b> | AMARILLO APP CON ★<br><b>119.5 307.0</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|-------------------------|------------------------------------------|---------------------------------|

