

WAAS
CH **65903**
W01A

APP CRS
007°

Rwy Idg **4206**
TDZE **794**
Apt Elev **798**

RNAV (GPS) RWY 1
SKYHAVEN (RCM)

RNP APCH - GPS.

▼

▲


Circling Rwy 32 NA at night. Baro-VNAV NA when using Whiteman AFB altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Rwy 1 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Knob Noster altimeter setting and increase LPV DA to 1083 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 1194 feet and all visibilities ½ SM. Increase all MDAs 40 feet and LNAV visibility Cat C ½ SM, and Circling visibility Cat C ½ SM.

MISSED APPROACH:
Climb to 3000 direct
FALIS and hold.

AWOS-3PT
119.575

WHITEMAN APP CON ★
127.45 284.0

UNICOM
123.0 (CTAF) 0



ELEV **798** TDZE **794**

REIL Rwys 1 and 19
REIL Rwys 14 and 32
MIRL Rwys 1-19 and 14-32

61	4206 X 75	2801 X 60	0.4% UP
----	-----------	-----------	---------

4 NM Holding Pattern

GP 3.00° TCH 36

BEJCY

CUCTO

YOCPU 1.7 NM to RW01

RW01

1883

CATEGORY	A	B	C	D
LPV DA	1044-1	250 (300-1)		NA
LNAV/VNAV DA	1155-1¼	361 (400-1¼)		NA
LNAV MDA	1220-1	426 (500-1)	1220-1¼ 426 (500-1¼)	NA
CIRCLING	1260-1 462 (500-1)	1340-1 542 (600-1)	1380-1½ 582 (600-1½)	NA

NC-3, 17 APR 2025 to 15 MAY 2025

NC-3, 17 APR 2025 to 15 MAY 2025