

WAAS
CH **99719**
W16A

APP CRS
164°

Rwy Idg
TDZE **99**
Apt Elev
100

RNAV (GPS) RWY 16

YOLO COUNTY (DWA)

RNP APCH.

When local altimeter setting not received, use Travis AFB altimeter setting and increase all DA 50 feet and all MDA 60 feet, and increase LNAV/VNAV all Cats and LNAV Cat C and D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). Baro-VNAV NA when using Travis AFB altimeter setting.

MISSED APPROACH: Climb to 3600 direct PROAP and hold, continue climb-in-hold to 3600.

AWOS-3P
125.775

TRAVIS APP CON
126.6 281.45

UNICOM
123.0 (CTAF)

Procedure NA for arrivals at ILA VORTAC airway radials 057 CW 210.

Procedure NA for arrivals at COUPS on V6 southbound.

MSA RW 16 25 NM

4300

3038

2430

3057

2368

(IAF) WILLIAMS ILA

3000 NoPT (18.8)

4 NM

164°

344°

(IAF) ELEGY

3000 NoPT 095° (11.3)

1996

(IF/IAF) GHEER

2000

(FAF) YOLOH

GAAAS 1.7 NM to RW16

220 ±

192 ±

4 NM

164°

344°

PROAP

3000 to GHEER 325° (29.8)

A-682

COUPS

ELEV 100

TDZE 99

164° to RW16

91

001 x 0009

34

MIRL Rwy 16-34

3600	PROAP	YOLOH	GHEER	4 NM Holding Pattern
*LNAV only	GAAAS 1.7 NM to RW16	2000	3000	
	1.7 NM	4.2 NM	6.2 NM	GP 3.00° TCH 40
CATEGORY	A	B	C	D
LPV DA	360-1 261 (300-1)			
LNAV/VNAV DA	402-1 303 (400-1)			
LNAV MDA	480-1 381 (400-1)		480-1½ 381 (400-1½)	