

WAAS CH 90117 W25A	APP CRS 254°	Rwy Idg 7281 TDZE 1475 Apt Elev 1478
--	------------------------	---

RNAV (GPS) RWY 25L


PHOENIX DEER VALLEY (DVT)

RNP APCH - GPS.


T When VGSI inop, Circling to Rwy 25R NA at night. Circling NA north of Rwy 7R-25L at night. When local altimeter setting not received, use Scottsdale altimeter setting; increase LPV all Cats DA to 1877 feet and LPV all Cats visibility $\frac{1}{8}$ SM. Increase all MDA 40 feet and Circling Cats B visibility $\frac{1}{4}$ SM. Rwy 25L helicopter visibility reduction below $\frac{3}{4}$ SM NA. VDP NA when using Scottsdale altimeter setting.

MISSED APPROACH: Climb to 6000 direct BOLES and on track 314° to HEVRO and right turn on track 072° to BANYO and hold.

ATIS 126.5	PHOENIX APP CON 120.7 239.0	DEER VALLEY TOWER★ 118.4 (070°-250°) (CTAF) 120.2 (251°-069°)	GND CON 121.8	CLNC DEL 123.9	UNICOM 122.95
----------------------	---------------------------------------	---	-------------------------	--------------------------	-------------------------



		tr 314°	tr 072°	
CATEGORY	A	B	C	D
LPV DA	1850-1¼		375 (400-1¼)	
LNAV MDA	2360-1¼ 885 (900-1¼)		2360-2¾ 885 (900-2¾)	2360-3 885 (900-3)
CIRCLING	2400-1¼ 922 (1000-1¼)	2420-1¼ 942 (1000-1¼)	2580-3 1102 (1200-3)	2700-3 1222 (1300-3)



RNAV (GPS) RWY 25L