

WAAS CH 45932 W11A	APP CRS 106°	Rwy Idg TDZE Apt Elev	3602 121 121
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 11


NEW KENT COUNTY (W96)

RNP APCH - GPS.

Procedure NA at night. Rwy 11 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use RIC altimeter setting: increase all MDAs 40 feet and LNAV visibility Cat C ½ SM; increase LP and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 2000 direct WINVO and hold.

AWOS-3 119.875	POTOMAC APP CON 126.4 282.375	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



4 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 45).

2000 WINVO

6000 2100

277° 097°

097°

DUTLE

3.77° TCH 60

1200

106°

RW11

6.4 NM 2.6 NM

ELEV 121

TDZE 121

106°

3602 X 75

0.4% UP

29

CATEGORY	A	B	C	D
LP MDA	540-1	419 (500-1)	540-1 ¼ 419 (500-1 ¼)	NA
LNAV MDA	560-1	439 (500-1)	560-1 ¼ 439 (500-1 ¼)	NA
CIRCLING	620-1	499 (500-1)	760-1 ¾ 639 (700-1 ¾)	NA

MIRL Rwy 11-29 0
REIL Rwy 11 and 29 0