

APP CRS
130°

Rwy Idg
TDZE
Apt Elev

3900
408
412

RNAV (GPS) RWY 13
FRANKLIN COUNTY (F53)

▼

▲ NA

DME/DME RNP-0.3 NA. Use Mount Pleasant Rgnl altimeter setting; if not received, procedure NA. Procedure NA at night. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 3000 direct FOSMA and hold.

OSA AWOS-3 119.775	FORT WORTH CENTER 132.025 360.75	UNICOM 123.0 (CTAF)
-----------------------	-------------------------------------	------------------------

The main chart displays the RNAV (GPS) RWY 13 approach. Key features include:

- Initial Descent:** From 3000 ft, a 3000 ft descent at 235° (15.5) leads to the LENYI fix.
- Intermediate Segment:** From LENYI, a 3000 ft descent at 290° (14.5) leads to the OSUYE fix.
- Final Segment:** From OSUYE, a 3000 ft descent at 310° (16.2) leads to the ICUKA fix.
- Altitudes:** 3000 ft at the start, 2000 ft at the ICUKA fix, and 500 ft at the RWY 13 threshold.
- Navigation Aids:** (IAF) PARIS PRX, (IAF) DUYAD, (IF/IAF) KEDEY, (FAF) ICUKA, and FOSMA.
- Obstacles:** 837 ft and 794 ft obstacles near the final segment, and a 1042 ft obstacle near FOSMA.
- MSA:** MSA RW 13 25 NM with a 2600 ft MSL.
- Other:** JAXAB fix, 519± ft obstacle, and 1042 ft obstacle.

ELEV 412 TDZE 408

130°

0.43 UP

3900 X 60

436

5

5 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 37).

3000

310°

130°

KEDEY

ICUKA

2000

3.04°

TCH 40

6.2 NM

4.9 NM

RW13

FOSMA

3000

4 NM

CATEGORY	A	B	C	D
LNAV MDA	820-1 412 (500-1)			NA
CIRCLING	940-1 528 (600-1)	980-1 568 (600-1)		NA

MOUNT VERNON, TEXAS
Orig-B 25MAR21

33°13'N-095°14'W

FRANKLIN COUNTY (F53)
RNAV (GPS) RWY 13

SC-2, 17 APR 2025 to 15 MAY 2025

SC-2, 17 APR 2025 to 15 MAY 2025