

WAAS CH 58041 W11A	APP CRS 111°	Rwy Idg 3200 TDZE 29 Apt Elev 29
--	------------------------	---

RNAV (GPS) RWY 11

BUCKLAND (BVK)(PABL)

RNP APCH.

▼


Baro-VNAV and VDP NA when using Selawik altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C.

▲

When local altimeter setting is not received use Selawik altimeter setting: increase DA to 387 feet and all visibilities $\frac{3}{8}$ SM; increase all MDAs 120 feet and visibility Cat C $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 3100 direct JAMUR and hold, continue climb-in-hold to 3100.

AWOS-3P 135.15	ANCHORAGE CENTER 119.2 263.0	KOTZEBUE RADIO 122.3	CTAF 122.9 0
--------------------------	--	--------------------------------	------------------------



JAMUR 		ELEV 29		TDZE 29	
4 NM Holding Pattern 6000 ← 290° 2900 → 110° GP 3.00° TCH 30 HAGVA BIHGO WIBLO 1.9 NM to RW11 *LNAV only. *0.9 NM to RW11 *660 7.7 NM 3.9 NM 1 NM 0.9 3100 JAMUR  111° to RW11 3200 X 75  29					
CATEGORY	A	B	C	D	
LPV DA	279-1 250 (300-1)			NA	
LNAV/VNAV DA	279-1 250 (300-1)			NA	
LNAV MDA	340-1 311 (400-1)			NA	
CIRCLING	540-1	511 (600-1)	640-1¾ 611 (700-1¾)	NA	MIRL Rwy 11-29 