

WAAS CH 82206 W15A	APP CRS 147°	Rwy Idg 11820 TDZE 504 Apt Elev 504
--	------------------------	--

RNAV (GPS) RWY 15



GRIFFISS INTL (RME)

RNP APCH-GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 48°C.
▲ When local altimeter setting not received, use Syracuse altimeter setting and increase LPV DA to 804 feet, LNAV/VNAV DA to 1152 feet and all MDA 100 feet. Increase LNAV/VNAV all Cats, LNAV Cats C and D and Circling Cats B and C visibility ¼ SM. Baro-VNAV and VDP NA when using Syracuse altimeter setting. Circling NA southwest of Rwy 15-33.

MISSED APPROACH: Climb to 3500 direct BOLTZ and hold.

ATIS 118.7	SYRACUSE APP CON 127.425 290.45	GRIFFISS TOWER ★ 118.1 (CTAF) 0 291.7	GND CON 121.9	UNICOM 122.95
----------------------	---	---	-------------------------	-------------------------



4 NM Holding Pattern				3500	BOLTZ
TURYN				2500	SCOUT
3500 ← 327°				147° →	147°
GP 3.00° TCH 55				2500	*1500
6.5 NM				3 NM	1.8 NM
1.2 NM				1.2 NM	1.2 NM
CATEGORY				A	B
LPV DA				704-1	200 (200-1)
LNAV/VNAV DA				1052-2	548 (600-2)
LNAV MDA				940-1 436 (500-1)	940-1¼ 436 (500-1¼)
CIRCLING				1140-1 636 (700-1)	1260-1 756 (800-1)
				1400-2¾ 896 (900-2¾)	1640-3 1136 (1200-3)

NE-2, 17 APR 2025 to 15 MAY 2025

NE-2, 17 APR 2025 to 15 MAY 2025