


AWOS-3P
135.75
NOME RADIO
122.05
ANCHORAGE CENTER
133.3 290.4
CTAF
122.9



NOTE: GPS required.
NOTE: RNAV 1.

TAKEOFF MINIMUMS

Rwy 3: Standard with minimum climb of 280' per NM to 1700.
Rwy 21: Standard with a minimum climb of 350' per NM to 2000.

TAKEOFF OBSTACLE NOTES

Rwy 3: Vertical structure and vegetation beginning 12' from DER, 9' right of centerline, up to 39' MSL.
Vertical structure, vegetation, and vehicles on road beginning 13' from DER, 21' left of centerline, up to 39' MSL.
Vehicles on road beginning 168' from DER, 80' left of centerline, up to 46' MSL.
Rwy 21: Vertical structure and vegetation beginning 12' from DER, 23' right of centerline, up to 8' AGL/64' MSL.
Vertical structure 55' from DER, 1' left of centerline, 60' MSL.
Vertical structure 443' from DER, 614' right of centerline, 22' AGL/78' MSL.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climb heading 026° to 557, then climbing left turn direct KUSEY, thence
TAKEOFF RUNWAY 21: Climb heading 206° to 557, then climbing right turn direct KUSEY, thence
. . . . on track 251° to OME VOR/DME, maintain 5000.