

APP CRS
031°

Rwy Idg
TDZE
Apt Elev

4000
648
658

RNAV (GPS) RWY 3

RUBY (RBY) (PARY)

When local altimeter setting not received, use Galena altimeter setting and increase all MDA 340 feet and all visibilities ¾ SM. DME/DME RNP-0.3 NA.
Rwy 3 Straight-in and Circling minimums NA at night. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:
Climbing right turn to 3800 direct WINUR and hold.

AWOS-3P 118.25	ANCHORAGE CENTER 127.0 290.2	FAIRBANKS RADIO 122.25	CTAF 122.8
-------------------	---------------------------------	---------------------------	---------------

The main chart displays the RNAV route for RWY 3. Key waypoints and data include:

- ZUMUN**: 30 NM to ZUMUN (5100), 10 NM to ZUMUN (3800). Altitude 1961.
- WINUR**: 30 NM to WINUR (NoPT) (3800). Altitude 1410.
- TINUC**: 3800 NoPT (6), 2700 (6.2), 030°. Altitude 1780.
- YARUN**: 2.9 NM to SOLCO, 881±.
- SOLCO**: 665±, 1087, 031°.
- DUCCEL**: 3800, 4600, 30 NM to DUCCEL, 10 NM to DUCCEL, 30°. Altitude 1780.

A missed approach procedure is shown as a climbing right turn to 3800 direct WINUR and hold. A 5 NM holding pattern is defined for WINUR with inbound 210° and outbound 030°.

5 NM Holding Pattern

WINUR

Visual Segment - Obstacles.

3800

WINUR

210°

030°

030°

2700

031°

1800

6.2 NM

3.2 NM

2.9 NM

0.1

CATEGORY	A	B	C	D
LNVA MDA	1260-1	612 (700-1)	1260-1¾ 612 (700-1¾)	NA
CIRCLING	1260-1 602 (700-1)	1400-1 742 (800-1)	1400-2¼ 742 (800-2¼)	NA

REIL Rwy 21

MIRL Rwy 3-21

RUBY, ALASKA

Amtd 1C 02DEC21

64°44'N-155°28'W

RUBY (RBY) (PARY)

RNAV (GPS) RWY 3