


MAYNR THREE DEPARTURE (RNAV)

TOP ALTITUDE:
ASSIGNED BY ATC



AUSTI
5000

202°

(26)

MAYNR

191°

(27)

MCLAW

243°

(28)

*1300

*15800

FL180

*1300

185°

(34)

FUNDI

265°

(36)

SLIPT

FL180

*1300

275°

(41)

JABOX

FL180

*1300

332°

(45)

MAXIM

FL180

*1300


261°

(41)

CANOA

TAKEOFF MINIMUMS
Rwy 10: Standard with minimum climb of 500'/NM to 2400.
Rwy 18: Standard with minimum climb of 500'/NM to 1800.
Rwy 28: Standard with minimum climb of 500'/NM to 1900.
Rwy 36: Standard with minimum climb of 500'/NM to 2200.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.



RNAV 1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1 - GPS.
From SLIPT to CANOA: RNAV 1 - GPS.
RADAR required for non-GPS equipped aircraft.
RADAR required.

MIAMI DEP CON
125.5 354.1
AWOS-3
118.375
CTAF
122.8

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

MAYNR THREE DEPARTURE (RNAV)