

RADAR MINS

25079

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BARKSDALE AFB (KBAD), LA (Bossier City) (Amdt 5, 15176 USAF)

ELEV 165

RADAR¹ - (E) 118.6 119.9 125.1 335.55 350.2

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR ²	15		AB	640/24	477	(500-½)
			CDE	640/50	477	(500-1)
	33		AB	640/24	479	(500-½)
			CDE	640/50	479	(500-1)
C CIR ³	ALL RWY		ABC	NOT AUTHORIZED		
			D	760-2	595	(600-2)
			E	780-2¼	615	(700-2¼)

¹Opr 1200-0500Z++.

²When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1½ miles.

³Circling not authorized W of Rwy.

GULFPORT, MS

Amdt 7A, 21MAR24 (24081) (FAA)

ELEV 28

GULFPORT-BILOXI INTL (GPT)

RADAR-1 127.5 254.25 **VA**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	32		ABCDE	440/40	413	(500-¾)				
	14		AB	560/24	533	(600-½)	CDE	560/55	533	(600-1¼)
C CIRCLING	ALL RWY		A	560-1	532	(600-1)	B	640-1	612	(700-1)
			C	820-2¼	792	(800-2¼)	D	820-2½	792	(800-2½)
			E	820-2¾	792	(800-2¾)				

When control tower closed, ASR NA.

For inoperative ALS, increase ASR S-14 CAT E to 1½ SM; and ASR S-32 A/B visibility to RVR 5500, and CAT C/D/E to RVR 6000.

Rwy 32 helicopter visibility reduction below RVR 4000 not authorized.

17 APR 2025 to 15 MAY 2025

17 APR 2025 to 15 MAY 2025

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

25079

N1

SC-4

RADAR MINS

25079

N2

RADAR INSTRUMENT APPROACH MINIMUMS

JACKSON, MS

Amdt 12A, 22APR21 (21112) (FAA)

ELEV 346

JACKSON-MEDGAR WILEY EVERS INTL (JAN)

RADAR-1 123.9 317.7 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	16L		AB	740/24	428	(400-½)	CDE	740/40	428	(400-¾)
	16R		AB	740-1	420	(400-1)	CDE	740-1½	420	(400-1½)
	34L		AB	820/40	491	(500-¾)	CDE	820/50	491	(500-1)
	34R		AB	840/55	494	(500-1¼)	CDE	840-1¾	494	(500-1¾)
C CIRCLING	ALL RWY		A	880-1	534	(600-1)	B	900-1	554	(600-1)
			C	900-1½	554	(600-1½)	D	960-2	614	(700-2)
			E	1040-2½	694	(700-2½)				

When control tower closed, procedure NA.

CAT E Circling not authorized southwest of runway 16R-34L.

Rwy 16L: For inoperative ALSF-2, increase Cat E visibility to RVR 6000.

Rwy 34L: For inoperative MALSR, increase Cat A/B visibility to RVR 5000, Cat C/D/E to 1%.

Rwy 16R, 34R: Helicopter visibility reduction below ¾ SM not authorized.

JOE WILLIAMS NOLF (KNJW), Moscow, MS Amdt 4 08SEP22 (22251) (USN)

ELEV 539

RADAR - (E) 134.1 266.8 300.4 310.8 322.0 325.2 328.4 346.0 363.6

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
ASR ¹	32		CD	1500-3	961	(1000-3)
CIR ¹	ALL RWY		CD	1500-3	961	(1000-3)

¹Procedure NA at night.

17 APR 2025 to 15 MAY 2025

17 APR 2025 to 15 MAY 2025

SC-4

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

25079

N2

RADAR MINS

25079

N3

RADAR INSTRUMENT APPROACH MINIMUMS

LAKE CHARLES, LA Amdt 1B, 31MAY12 (14149) (FAA) ELEV 17
CHENNAULT INTL (CWF)
 RADAR-1 119.8 282.3 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	33		AB	580-1	564	(600-1)	CDE	580-1^{5/8}	564	(600-1 ^{5/8})
	15		AB	620-^{3/4}	606	(700- ^{3/4})	CDE	620-1^{1/8}	606	(700-1 ^{1/8})
CIRCLING	ALL RWY		AB	640-1	623	(700-1)	C	640-1^{3/4}	623	(700-1 ^{3/4})
			D	640-2	623	(700-2)	E	880-3	863	(900-3)

When local altimeter setting not received, use Lake Charles Rgnl altimeter setting and increase all MDA 20 feet.

For inoperative MALSR, increase ASR 15 CATs A/B visibility to 1 and CATs C/D/E to 1^{1/4}.

Rwy 15: visibility reduction by helicopters NA.

Procedure not available when Lake Charles approach control closed.

LAKE CHARLES, LA Amdt 5D, 05NOV20 (20310) (FAA) ELEV 15
LAKE CHARLES RGNL(LCH)
 RADAR-1 119.35 353.75 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	33		ABC	380-^{3/4}	369	(400- ^{3/4})	D	380-1^{1/4}	369	(400-1 ^{1/4})
	5		ABC	380-1	366	(400-1)	D	380-1^{1/4}	366	(400-1 ^{1/4})
	15		AB	440/24	428	(500- ^{1/2})	C	440/40	428	(500- ^{3/4})
			D	440/50	428	(500-1)				
	23		AB	440-1	425	(500-1)	CD	440-1^{1/4}	425	(500-1 ^{1/4})
C CIRCLING	ALL RWY		A	440-1	425	(500-1)	B	480-1	465	(500-1)
			C	580-1^{1/2}	565	(600-1 ^{1/2})	D	680-2	665	(700-2)

When control tower closed, ASR NA.

MAKS AAF (KPOE), Fort Johnson, LA RADAR 1 Amdt 4C RADAR 2 Orig ELEV 330
 (23362) USA
 RADAR - (E) 123.7 261.3 **▽** NA Opr 1400-0600Z++ exc hol.

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR ¹	34	3.0°/42/799	AB	579-^{1/2}	256	(300- ^{1/2})
			CD	579-^{3/4}	256	(300- ^{3/4})
ASR	34		AB	760-^{3/4}	482	(500- ^{3/4})
			CD	760-1	482	(500-1)
	16		AB	800-1	472	(500-1)
			CD	800-1^{5/8}	472	(500-1 ^{5/8})
CIR	ALL RWY		AB	820-1	490	(500-1)
			C	820-1^{1/2}	490	(500-1 ^{1/2})
			D	880-2	550	(600-2)

¹Rwy 34 VGSI and PAR glidepath not coincident.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

25079

N3

SC-4


17 APR 2025 to 15 MAY 2025

17 APR 2025 to 15 MAY 2025

RADAR INSTRUMENT APPROACH MINIMUMS

MERIDIAN NAS (MC CAIN FIELD) (KNMM), Meridian, MS Amdt 6

29DEC22 (22363) (USN)

RADAR - (E) 134.1 235.625 236.825 244.875 256.875 266.8 310.8 323.225 328.4 

ELEV 316

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ¹	19L	3.0°/50/1178	ABCDE	416 -½	100	(100-½)
	1L ²	3.0°/50/1079	ABCDE	454 -½	200	(200-½)
	1R	3.0°/50/1151	ABCDE	470 -¾	200	(200-¾)
	19R	3.0°/50/1180	ABCDE	494 -¾	200	(200-¾)
PAR W/O GS ¹	19R ³		AB	700 -1	406	(400-1)
			CDE	700 -1½	406	(400-1½)
	1L ^{4,5}		AB	760 -½	506	(500-½)
ASR ⁶			CDE	760 -1	506	(500-1)
	28 ⁷		ABCDE	680 -1	375	(400-1)
	1R ⁸		AB	700 -1	430	(400-1)
			CDE	700 -1¼	430	(400-1¼)
	1L ^{4,9}		AB	760 -½	506	(500-½)
			CDE	760 -1	506	(500-1)
	19L ⁴		AB	780 -½	464	(500-½)
			CDE	780 -1	464	(500-1)
	19R ¹⁰		AB	720 -1	426	(500-1)
			CDE	720 -1¼	426	(500-1¼)
	10 ¹¹		AB	740 -1	436	(500-1)
		CDE	740 -1¼	436	(500-1¼)	
CIR	All Rwy		A	820 -1	504	(600-1)
			B	840 -1	524	(600-1)
			C	840 -1½	524	(600-1½)
			D	880 -2	564	(600-2)
			E	1080 -2¾	764	(800-2¾)

17 APR 2025 to 15 MAY 2025

17 APR 2025 to 15 MAY 2025

¹No-NOTAM MP sked: PAR 1300-1700Z++ Tue. PAR and PAR W/O GS apch not avbl dur this time.

²When ALS inop, increase vis to ¾ mile.

³Step Down at 2 NM from thld, 860 min.

⁴When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1¾ miles.

⁵Step Down at 3 NM from thld, 1140 min.

⁶No-NOTAM MP sked: DASR 11 1300-1700Z++ Tue. No ASR apch dur this time.

⁷Step Down at 2 NM from thld, 980 min.

⁸Step Down at 3 NM from thld, 1080 min.

⁹Step Down at 2.5 NM from thld, 1020 min.

¹⁰Step Down at 2 NM from thld, 880 min.

¹¹Step Down at 3 NM from thld, 1220 min.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

25079

N5

RADAR INSTRUMENT APPROACH MINIMUMS

MONROE, LA

Amdt 7B, 08OCT20 (20282) (FAA)

ELEV 79

MONROE RGNL (MLU)

RADAR- 1 118.15 290.475 **▼** **A**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	4		AB	560/40	484	(500-¾)	CD	560/50	484	(500-1)
	22		AB	560-¾	485	(500-¾)	CD	560-1	485	(500-1)
C CIRCLING ALL RWY			AB	580-1¼	501	(600-1¼)	C	740-1¾	661	(700-1¾)
			D	1160-3	1081	(1100-3)				

When control tower closed, ASR NA.

Circling Rwy 14 NA at night.

For inop ALS: increase S-4 Cat A/B visibility to RVR 5500, Cat C/D visibility to 1 ¾ SM. Increase S-22 Cat A/B visibility to 1 SM and Cat C/D visibility to 1 ¾ SM.

NEW ORLEANS NAS JRB (ALVIN CALLENDER FLD) (KNBG),

New Orleans, LA Amdt 6 20MAR25 (25079) (USN)

ELEV 2

RADAR¹ - (E) 125.95 126.55 225.5 254.4 269.025 288.25 299.2 353.65 **▼**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR	4 ²	3.0°/49/928	ABCDE	98-¼	100	(100-¼)
	22 ^{3,4}	3.0°/41/816	ABCDE	200-½	200	(200-½)
PAR W/O GS	4 ^{5,6}		AB	460-½	462	(500-½)
			CDE	460-1	462	(500-1)
	22 ^{6,7,8}		ABCDE	380-½	380	(400-½)
ASR	4 ^{6,9}		AB	600-½	602	(600-½)
			CDE	600-1%	602	(600-1%)
	22 ^{6,9,10}		AB	600-½	600	(600-½)
			CDE	600-1¼	600	(600-1¼)
	32 ^{6,11,12}		AB	580-¾	578	(600-¾)
			CDE	580-1%	578	(600-1%)
C CIR ⁶	Rwy 04/22/32		AB	640-1	638	(700-1)
			C	640-1¼	638	(700-1¼)
			D	660-2	658	(700-2)
			E	680-2½	678	(700-2½)

¹No-NOTAM preventive maint Mon 1300-1800Z++.

²When ALS inop, increase vis to ½ mile.

³When ALS inop, increase vis to ¾ mile.

⁴CAUTION: TCH (41') is less than min TCH (45') for aircraft similar to B-747/767/720/757, DC-10, A-300, KC-10, E-4, C-5 and VC-25.

⁵When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1% miles.

⁶CAT E circling not authorized NW of Rwy 4-22.

⁷When ALS inop, increase vis to 1 mile.

⁸Step Down Fix at 2 NM from RPI, 660 min.

⁹When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¼ miles.

¹⁰Step Down Fix at 3 NM from thld, 1000 min.

¹¹When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1% miles.

¹²Rwy 32 helicopter vis reduction below ¾ mile not authorized.

17 APR 2025 to 15 MAY 2025

17 APR 2025 to 15 MAY 2025

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

25079

N5

SC-4

RADAR INSTRUMENT APPROACH MINIMUMS

SHREVEPORT, LA

Amdt 6A, 05NOV20 (20310) (FAA)

ELEV 258

SHREVEPORT RGNL (SHV)

RADAR-1 119.9 335.55 **T A**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	32		AB	720/40	498	(500-¾)
			CDE	720/50	498	(500-1)
			AB	800/40	542	(600-¾)
	14		CDE	800/60	542	(600-1¼)
			AB	800-1¼	562	(600-1¼)
			CDE	800-1½	562	(600-1½)
C CIRCLING	ALL RWY	AB	800-1¼	542	(600-1¼)	
		C	980-2	722	(800-2)	
		D	1100-2¾	842	(900-2¾)	
		E	1100-3	842	(900-3)	

Rwy 6, 32 helicopter visibility reduction below ¾ SM NA.

For inoperative ALS, increase S-14 Cat E visibility to 1% SM and S-32 Cat C/D/E visibility to 1% SM.

When control tower closed, ASR NA.

17 APR 2025 to 15 MAY 2025

17 APR 2025 to 15 MAY 2025

RADAR INSTRUMENT APPROACH MINIMUMS