



WAAS CH 99723 W13B	APP CRS 133°	Rwy Idg 7352 TDZE 485 Apt Elev 487
--	------------------------	---

RNAV (GPS) Z RWY 13L
DALLAS LOVE FLD (DAL)

RNP APCH.					MALSR		MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct SOLDO and hold.		
Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -6°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cats C/D visibility to RVR 5500.									
D-ATIS 120.15		LONE STAR APP CON NORTH 124.3 282.275 SOUTH 125.2 343.65		LOVE TOWER 123.7 239.3		GND CON 121.75 348.6		CLNC DEL 127.9	CPDLC



WADES 2500		NNATE 1900		TSKED 1.4 NM to RW13L	
GP 3.00° TCH 55		1900		*980	
8.7 NM		2.9 NM		1.4 NM	
CATEGORY	A	B	C	D	
LPV DA	685/18		200 (200-½)		
LNAV/VNAV DA	764/24		279 (300-½)		
LNAV MDA	840/24		355 (400-½)		840/30 355 (400-¾)
CIRCLING	1000-1 513 (600-1)	1140-1 653 (700-1)	1220-2 733 (800-2)	1520-3 1033 (1100-3)	