


LOC/DME I-FCN 111.1 Chan 48	APP CRS 251°	Rwy ldg TDZE Apt Elev	25R	25L
			11134	11095
			104	104
			128	128

ILS or LOC RWY 25R
LOS ANGELES INTL (LAX)

From CRCUS, SEAVU, TRNDO, CLPUR: RNAV 1-GPS required. DME or RADAR required.		MALSR Rwy 25R	ALSF-2 Rwy 25L	MISSED APPROACH: Climb to 2000 on heading 251° until crossing SMO R-160 then left turn on heading 236° and SMO VOR/DME R-195 to CATLY INT/SMO 15.7 DME and hold.
Simultaneous approach authorized. Simultaneous approach authorized with HHR. For inop ALS increase Sidestep 25L Cat C visibility to 1½ SM. #RVR 1800 authorized with use of FD or AP or HUD to DA.				

D-ATIS ARR 133.8 DEP 135.65	SOCAL APP CON 124.3 363.2 [ARCH FM WEST] [225°-044°]	124.9 269.0 [090°-224°]	LOS ANGELES TOWER N 133.9 239.3 S 120.95 379.1	GND CON N 121.65 327.0 S 121.75 327.0 W 121.4 327.0	CLNC DEL 120.35 327.0	CPDLC
---	--	-----------------------------------	--	---	---	-------



CATEGORY	S-ILS 25R#			
	304/24 200 (200-½)			
	S-LOC 25R			
	700/24 596 (600-½) 700-1¼ 596 (600-1¼)			
SIDESTEP 25L	700/55 596 (600-1) 700-1¼ 596 (600-1¼) 700-1½ 596 (600-1½)			

ELEV 128	TDZE 25R 104	TDZE 25L 104
TDZ/CL Rwyys 6R, 7L, 24R, and 25L HIRL all Rwyys		
FAF to MAP 5.5 NM		
Knots	60	90 120 150 180
Min:Sec	5:30	3:40 2:45 2:12 1:50

SW-3, 15 MAY 2025 to 12 JUN 2025

SW-3, 15 MAY 2025 to 12 JUN 2025