PATUXENT RIVER, MARYLAND

RNAV (GPS) RWY 14

APCH CRS 136°	Rwy ldg 9732 TDZE 27 Arpt Elev 39

- (USN) PATUXENT RIVER NAS (TRAPNELL FLD) (KNHK)

RNP APCH

RADAR required

MISSED APPROACH: Climb to 600, then climbing left turn to 2500 direct SPRIG and hold.

ATIS	APP CON/DEP CON★	TOWER	GND CON	CLNC DEL	ASR/PAR
322.425	121.0 250.3	123.7 343.65	120.6 336.4	135.2 316.125	

For uncompensated Baro-VNAV systems, Procedure NA below -15°C (5°F) or above 54°C (129°F).

CAUTION: WCH group 4 acft: 16 feet is less than minimum 20 feet.

MISSED APPROACH
8 NM
055°
235°
HOLD 8000/2500
SPRIG

HOLD 8000/2500
136°
316°
8 NM
201
(IF/IAF) STEVR
1600
136°
(6)
475
(FAF) KOSSE
R4007
ST MARYS COUNTY RGNL
300
MSA RW14 25 NM
2000
2500
317°
(1.8)
NHK to STEVR
291
RW14
NAS PATUXENT RIVER NHK
EMERG SAFE ALT 100 NM 5100

8 NM Holding Pattern
8000/2500
316°
STEVR
136°
136°
KOSSE
1600
1.4 NM to RW14
RW14
GP 3.00°
TCH 41
4.8 NM
600
2500
SPRIG

ELEV 39
TDZE 27
136°
126
11,799 x 200
9732 x 200
5021 x 75
0.3% UP
20
TWR 236
BCN
2
6
24
32
A1

CATEGORY	A	B	C	D	E
LNAV/VNAV DA	367-1 340 (400-1)	378-1 351 (400-1)	386-1 359 (400-1)	397-1 370 (400-1)	
LNAV MDA	500-1 473 (500-1)		500-1⅜ 473 (500-1⅜)		
C CIRCLING	540-1 501 (600-1)	560-1 521 (600-1)	620-1½ 581 (600-1½)	680-2 641 (700-2)	820-2¾ 781 (800-2¾)

HIRL Rwys 6-24, 14-32
TDZL/CL Rwy 6

NE-3, 15 MAY 2025 to 12 JUN 2025