

|                                        |                        |                                                                 |
|----------------------------------------|------------------------|-----------------------------------------------------------------|
| WAAS<br>CH <b>72905</b><br><b>W04A</b> | APP CRS<br><b>039°</b> | Rwy Idg <b>5000</b><br>TDZE <b>2885</b><br>Apt Elev <b>2885</b> |
|----------------------------------------|------------------------|-----------------------------------------------------------------|

RNAV (GPS) RWY 4  
LIBERAL MID-AMERICA RGNL (LBL)

RNP APCH - GPS.

**▼** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C.  
**▲** Circling NA east of Rwy 17-35. When local altimeter setting not received, use GUY altimeter setting and increase LPV DA to 3248 feet; increase LNAV/VNAV DA to 3412 feet and all visibilities  $\frac{3}{8}$  SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D  $\frac{3}{8}$  SM, and Circling visibility Cat C/D  $\frac{1}{4}$  SM. Baro-VNAV and VDP NA when using GUY altimeter setting.

**MISSED APPROACH:** Climb to 4800 direct NULEE and hold.

AWOS-3PT  
118.375

KANSAS CITY CENTER  
134.0 257.625

UNICOM  
122.8 (CTAF) **L**