12 JUN 2025

<u>۔</u>

SC-1, 15 MAY 2025

## STPHN THREE DEPARTURE (RNAV)

## **TOP ALTITUDE:** ATIS TAKEOFF MINIMUMS: 128.725 ASSIGNED BY ATC Rwys 13, 17L/R, 31, 35L/R: GND CON Standard with minimum climb WILEY POST TOWER \* of 500' per NM to 2100. 126.9 306.9 OKE CITY DEP CON 124.6 266.8 1800 7000 6000 4200 3400 3400 3100 (20)**ZEEWE** (27)**BFFFY** (4)**STPHN SQRRL** 1800 1800 NOTE: RADAR required. NOTE: DME/DME/IRU or GPS required.

NOTE: Chart not to scale

NOTE: RNAV 1.



## DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 13: Climb heading 131° to 1800, then right turn heading 201° or as assigned by ATC, expect RADAR vectors to SQRRL, thence . . . . TAKEOFF RWYS 17L/R: Climb on heading 176° to 1800, then right turn heading 201° or as assigned by ATC, expect RADAR vectors to SQRRL, thence . . . . TAKEOFF RWY 31: Climb on heading 311° to 1800, then heading 311° or as assigned by ATC, expect RADAR vectors to SQRRL, thence . . . . TAKEOFF RWYS 35L/R: Climb on heading 356° to 1800, then left turn heading 311° or as assigned by ATC, expect RADAR vectors to SQRRL, thence . . . .

. . . . on track 272° to STPHN, then on (transition). Maintain 3000 or as assigned by ATC. Expect filed altitude 10 minutes after departure.

BFFFY TRANSITION (STPHN3.BFFFY): ZEEWE TRANSITION (STPHN3.ZEEWE):