


LOC/DME I-HNL	APP CRS	Rwy Idg	12312
111.7	079°	TDZE	14
Chan 54		Apt Elev	14

LOC RWY 8L


DANIEL K INOUE INTL (HNL) (PHNL)

DME or RADAR required.		MALSR	MISSED APPROACH: Climbing right turn to 5000 on heading 200° and HNL VORTAC R-171 to ALANA INT/HNL 13.9 DME and hold, continue climb-in-hold to 5000.
Circling Rwy 22R NA at night. Circling NA for Cats A and B northwest of Rwys 8L and 22R and for Cats C and D north of Rwy 8L-26R. Circling NA to sea lanes 4W, 8W, 22W and 26W. For inop ALS, increase S-LOC 8L Cats C and D visibility to 1½ SM.			

D-ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL
127.9 251.15	118.3 269.0	118.1 257.8 123.9 273.575 (Rwy 8R/26L)	121.9 348.6	121.4 281.4



ELEV 14	D	TDZE 14
MIRL Rwy 4L-22R		
REIL Rwys 4L, 8R, 22L, 22R, and 26R		
HIRL Rwys 4R-22L, 8L-26R, and 8R-26L		



FAF to MAP 5.9 NM		CIGEP I-HNL 15.3 RADAR		VGSi and descent angles not coincident (VGSi Angle 3.00/TCH 73).		5000	HNL R-171	ALANA
		FEGTU I-HNL 9.5 RADAR		EWABE LOM I-HNL 8.1 RADAR		hdg 200°		
		3600		2400		2000		
		5.9 NM		1.4 NM		4.7 NM		Use I-HNL DME when on the localizer course.
		079°		3.08°		TCH 56		
		I-HNL 3.4		I-HNL 2.2				
		CATEGORY		A		B		C
		S-8L		480-½		466 (500-½)		480-1
		CIRCLING		680-1		666 (700-1)		820-2¼
								806 (900-2¼)
								1280-3
								1266 (1300-3)