


APP CRS	Rwy ldg	8200
047°	TDZE	32
	Apt Elev	32

RNAV (GPS) RWY 5
PAGO PAGO INTL (PPG) (NSTU)

RNP APCH.	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 22°C or above 54°C. When local altimeter setting not received, procedure NA. Circling NA northwest of Rwy 5-23. Rwy 5 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to LNAV Cats A/B. For inop ALS, increase LNAV/VNAV all Cats visibility to 1¾ SM and LNAV Cats C/D visibility to 2 SM.	MALSRL	MISSED APPROACH: (Maintain 185 K max until 760) Climb to 760 then climbing right turn to 4000 direct DRAWN and hold.
-----------	---	--------	---

FALEOLO APP CON 118.1 6.553 (HF)	CTAF 122.9	118.30
-------------------------------------	---------------	--------



4 NM Holding Pattern	VGSI and RNAV glidepath not coincident (VGSI Angle 3.25/TCH 57).	760	4000	DRAWN
GRUPY	BLUJA	CAXEB	HOPID	
3700	2300	2300	2300	
GP 3.25° TCH 51	6.5 NM	4.2 NM	2 NM	0.2
CATEGORY	A	B	C	D
LNAV/VNAV DA	551-1	519 (600-1)		
LNAV MDA	760-1	728 (800-1)	760-1½	728 (800-1½)
CIRCLING	760-1	728 (800-1)	820-2¼ 788 (800-2¼)	860-2¾ 828 (900-2¾)