

SCRAM SIX DEPARTURE (RNAV)

TOP ALTITUDE:
3000



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 1L/C/R, 19L/C/R, 30: Climb on heading assigned by ATC, expect RADAR vectors to POOCH, then on track 240° to SCRAM, thence. . .

... as depicted. Maintain 3000. Expect clearance to filed altitude within ten (10) minutes after departure.

GLANC TRANSITION (SCRAM6.GLANC):

D-ATIS	1134.85
CLINC D	1135.7
CPDLC	
GND CC	1121.9
DULLES	1121.62
	1120.1
	1120.25
POTOM	1134.42
	1126.65

TAKEOFF MINIMUMS:

Rwys 1L/C/R, 19L/C/R, 30:

Standard with a minimum climb of 500' per NM to 820.

NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: Turbo-jets only.

NOTE: Chart not to scale.

NE-3, 15 MAY 2025 to 12 JUN 2025

SCRAM SIX DEPARTURE (RNAV)

(SCRAM6.SCRAM) 31DEC20

WASHINGTON, DC
WASHINGTON DULLES INTL (IAD)