

WAAS	APP CRS	Rwy Idg	10702
CH 65817	334°	TDZE	17
W33A		Apt Elev	17

RNAV (GPS) RWY 33

CHENNAULT INTL (CWF')

RNP APCH - GPS.



▼

ASR

Baro-VNAV and VDP NA when using Lake Charles Rgnl altimeter setting.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.
When local altimeter setting not received, use Lake Charles Rgnl altimeter setting and increase LPV DA to 233 feet; increase LNAV/VNAV DA to 510 feet and all visibilities ½ SM.
Increase all MDAs 20 feet and LNAV visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 2000 direct CEVKU and hold.

ATIS	LAKE CHARLES APP CON ★	CHENNAULT TOWER ★	GND CON	UNICOM
120.0	119.8 282.3	124.2 (CTAF) 0 290.4	121.65 275.8	122.95



2000	CEVKU			
		GOGNE	FERDU	4 NM Holding Pattern
		1.6 NM to RW33	1700	154° 6000 334° 2000
		1.6	3.5 NM	6 NM
RW33				
				GP 3.00° TCH 53
CATEGORY	A	B	C	D
LPV DA		217-3/4	200 (200-3/4)	
LNAV/VNAV DA		494-13/4	477 (500-13/4)	
LNAV MDA	580-1	563 (600-1)	580-15/8	563 (600-15/8)
CIRCLING	640-1	623 (700-1)	640-13/4 623 (700-13/4)	740-21/4 723 (800-21/4)