

LOC I-ECC <u>110.1</u>	APP CRS 200°	Rwy Idg 8653 TDZE 5605 Apt Elev 5622
----------------------------------	------------------------	---

ILS or LOC RWY 20
CEDAR CITY RGNI (CDC)

DME required.

T	XOJPO fix minimums (Dual VOR receivers required): For inop ALS, increase S-LOC 20 Cats C/D visibility to 1 $\frac{3}{8}$ SM. For inop ALS, increase S-LOC 20 Cats C/D visibility to 2 $\frac{1}{2}$ SM.
----------	---

#For inop ALS, increase S-ILS 20 visibility all Cats to 1 SM.


MALSR



MISSED APPROACH: Climb to 6200 then climbing right turn to 10000 on heading 322° and on EHK R-278 to BERYL INT/EHK 16.5 DME and hold, continue climb-in-hold to 10000.

† Missed approach requires minimum climb of 210 feet per NM to 7300.

ASOS 119.025	SALT LAKE CITY CENTER 125.575 379.275	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------



STAR Procedure Data:

Category	A	B	C	D
S-ILS 20†	5825-1/2 220 (300-1/2)			
S-ILS 20#	5882-1/2 277 (300-1/2)			
S-LOC 20	6440-1/2 835 (900-1/2)	6440-3/4 835 (900-3/4)	6440-1 7/8 835 (900-1 7/8)	

Vertical Profile Data:

Distance (NM)	Altitude (ft)
2.4	200
4.3	7800
2.9	7800

FAF to MAP: 6.7 NM

Knots	60	90	120	150	180
Min:Sec	6:42	4:28	3:21	2:41	2:14