


WAAS CH 69630 W05A	APP CRS 050°	Rwy Idg TDZE 3427 Apt Elev 3443
--	------------------------	---

RNAV (GPS) RWY 5

SHELBY (SBX)

RNP APCH - GPS.	MISSED APPROACH: Climb to 9000 direct YENUP and hold, continue climb-in-hold to 9000.
▼ Baro-VNAV and VDP NA when using Cut Bank altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use Cut Bank altimeter setting.	

AWOS-3PT 128.325	SALT LAKE CITY CENTER 133.4 285.4	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------



7 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 29).		9000	YENUP
14000 7000		CAVBU		IXIPE	
GP 3.00° TCH 45		5100		UZOHU 2.7 NM to RW05	
7 NM		2.4 NM		1.1 NM to RW05	
CATEGORY	A	B	C	D	
LPV DA		3733-1	306 (300-1)		
LNAV/VNAV DA		3783-1	356 (400-1)		
LNAV MDA		3800-1	373 (400-1)		
CIRCLING	4020-1 577 (600-1)	4080-1 637 (700-1)	4100-1 657 (700-1 1/4)	4220-2 777 (800-2 1/2)	