

LOC I-GLR <u>111.1</u>	APP CRS 096°	Rwy Idg 6579 TDZE 1321 Apt Elev 1328
----------------------------------	------------------------	---

ILS or LOC RWY 9
GAYLORD RGNL (GLR)

--	--

ADF required. RADAR required for procedure entry.

V Circling Rwy 18, 36 NA at night. When local altimeter setting not received, use GOV altimeter setting and increase S-ILS 9 D to 1591 feet; increase all MDAs 80 feet and S-LOC 9 visibility Cat C and D $\frac{3}{4}$ SM, and Circling visibility Cat C and D $\frac{1}{4}$ SM. For inop ALS when using GOV altimeter setting, increase S-ILS 9 all Cats visibility to $\frac{3}{4}$ SM and S-LOC 9 Cats C and D visibility to $1\frac{3}{4}$ SM. For inop ALS, increase S-LOC 9 Cats C and D visibility $\frac{3}{4}$ SM.


MALSR

MISSED APPROACH: Climb to 3000 then left turn direct BANGU LOM and hold.

ASOS
118,375

MINNEAPOLIS CENTER
134.6 354.05

UNICOM
122.8 (CTAF) **L**



Remain
within 10 NM

GL
LOM
RADAR

3000

GL

VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 38).

$$\frac{\text{GS } 3.00^\circ}{\text{TCH } 50}$$

CATEGORY	A	B	C	D
S-ILS 9	1521-½		200 (200-½)	
S-LOC 9	1860-½ 539 (600-½)		1860-1 539 (600-1)	
 CIRCLING	1860-1 532 (600-1)	1940-1 612 (700-1)	2040-2 712 (800-2)	2040-2½ 712 (800-2½)

HIRL Rwy 9-27 **L**
MIRL Rwy 18-36 **L**
REIL Rwys 18, 27 and 36 **L**

FAF to MAP 3.9 NM

Knots	60	90	120	150	180
Min:Sec	3:54	2:36	1:57	1:34	1:18