

WAAS CH 78033 W15A	APP CRS 146°	Rwy Idg TDZE 1139 Apt Elev 1160
--	------------------------	---

RNAV (GPS) RWY 15

BOONE MUNI (BNW)

RNP APCH.


▼

▲

Baro-VNAV and VDP NA when using Ames Muni altimeter setting. For uncompensated Baro-VNAV Systems, LNAV/VNAV NA below -22°C or above 54°C. Rwy 15 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Ames Muni altimeter setting and increase all DA 54 feet and all MDA 60 feet. Increase LNAV/VNAV all Cats visibility to 1½ mile. Circling NA to Rwy 2 and 20.

MISSED APPROACH:
Climb to 4000 direct CALUM and hold.

AWOS-3 120.925	DES MOINES APP CON 123.9 307.15	UNICOM 123.0 (CTAF)
--------------------------	---	-------------------------------



ELEV 1160

 TDZE 1139

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).

HOPWO

DETRO

LOCEC 2.5 NM to RW15

*INAV only

*1960

RW15

GP 3.00° TCH 40

3000

2800

2600

2400

2200

2000

1800

1600

1400

1200

1000

800

600

400

200

0

CATEGORY	A	B	C	D
LPV DA	1401-1	262 (300-1)		NA
LNAV/VNAV DA	1643-1¾	504 (500-1¾)		NA
LNAV MDA	1580-1	441 (500-1)		NA
CIRCLING	1620-1 460 (500-1)	1640-1 480 (500-1)		NA

REIL Rwy 15

MRL Rwy 15-33