

CTAF
122.8
HOUSTON DEP CON
134.45 284.0

(HOODO7.HOODO) 21280 AL-5757 (FAA)
HOODO SEVEN DEPARTURE (RNAV)

BAYTOWN (HPY)
BAYTOWN, TEXAS

TOP ALTITUDE:
ASSIGNED BY ATC

NOTE: RNAV 1.

NOTE: RADAR required.


NOTE: ATC assigned only.

NOTE: DME/DME/IRU or GPS required.

NOTE: For non-GPS equipped aircraft, LCH, ILA, TBD, and LEV DME's must be operational.

TAKEOFF MINIMUMS

Rwys 14, 32: Standard with minimum climb of 500' per NM to 540.



SCHOLES
VUH

2300
*1400

118°

(32)

HOODO

SBIRD

CFOOD

BOWFN

LEEVILLE

HARVEY

11000

*1700

076°

(60)

(82)

*2100

11000

048°

(60)

LEEVILLE

HARVEY

11000

*1700

076°

(60)

LEEVILLE

HARVEY

11000

*2100

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 14: Climb on heading 140° to 540, for RADAR vectors to VUH VOR/DME, thence

TAKEOFF RUNWAY 32: Climb on heading 320° to 540, for RADAR vectors to VUH VOR/DME, thence

. . . . on track 118° to HOODO, then on (transition). Maintain ATC assigned altitude.
Expect filed altitude 10 minutes after departure.

- BOWFN TRANSITION (HOODO7.BOWFN)
- CFOOD TRANSITION (HOODO7.CFOOD)
- HARVEY TRANSITION (HOODO7.HRV)
- LEEVILLE TRANSITION (HOODO7.LEV)
- SBIRD TRANSITION (HOODO7.SBIRD)

HOODO SEVEN DEPARTURE (RNAV)
(HOODO7.HOODO) 07OCT21

BAYTOWN, TEXAS
BAYTOWN (HPY)