

WAAS
CH **86935**
W01A

APP CRS
009°

Rwy Idg
TDZE **499**
Apt Elev **499**

RNAV (GPS) RWY 1

WILLIAM L WHITEHURST FLD (M08)

▼

⚠

NA

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson altimeter setting and increase all MDA 80 feet, increase LP Cats C/D visibilities $\frac{3}{8}$ mile, and LNAV Cats C/D and Circling Cats C/D visibilities $\frac{1}{4}$ mile. Rwy 1 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 2500 direct HESKA and hold.

AWOS-3 121.125	MEMPHIS CENTER 124.35 318.1	UNICOM 123.0 (CTAF)
--------------------------	---------------------------------------	-------------------------------

The chart displays the RNAV (GPS) RWY 1 approach. Key features include:

- Missed Approach:** Climb to 2500 direct HESKA and hold. HESKA is located 4 NM from the missed approach fix.
- Altitudes:** Various altitudes are marked, including 621, 619±, 601±, 920, 2000, 1040, and 189.
- Distances:** Distances are marked in NM, including 30 NM to HOMOB, 1.4 NM to RW01, 4 NM, and 6.6 NM.
- Obstacles:** Obstacles are marked with their MSL and AGL altitudes, including 2500, 189, 1040, and 189.
- Visual Segment - Obstacles:** A section showing the visual segment with obstacles and altitudes.

4 NM Holding Pattern		Visual Segment - Obstacles.		2500	HESKA
2500		LOHNI		SADJI	JUSES
189°		009°		1.4 NM to RW01	RW01
009°		2000		1040	
6.6 NM		2.6 NM		1.4 NM	
CATEGORY	A	B	C	D	
LP MDA	860-1 361 (400-1)				
LNAV MDA	880-1	381 (400-1)	880-1 $\frac{1}{8}$	381 (400-1 $\frac{1}{8}$)	
CIRCLING	980-1	481 (500-1)	1100-1 $\frac{3}{4}$ 601 (700-1 $\frac{3}{4}$)	1360-2 $\frac{3}{4}$ 861 (900-2 $\frac{3}{4}$)	

BOLIVAR, TENNESSEE

Amdt 1A 22JUN17

35°13'N - 89°03'W

WILLIAM L WHITEHURST FLD (M08)

RNAV (GPS) RWY 1