


WAAS CH 82536 W28A	APP CRS 281°	Rwy Idg TDZE 435 Apt Elev 435	5010
--	------------------------	---	-------------


RNAV (GPS) RWY 28
CLAYTON MUNI (11A)

RNP APCH - GPS.		MISSED APPROACH: Climb to 2200 direct YARCU and hold.
▼ Rwy 28 helicopter visibility reduction below ¾ SM NA. Use Eufaula altimeter setting; ▲ NA when not received, use Troy altimeter setting.		

EUF ASOS 128.325	CAIRNS APP CON ★ 121.1 319.25	CTAF 122.90
----------------------------	---	-----------------------



ELEV 435	TDZE 435
-----------------	-----------------



2200		YARCU		VGS and descent angles not coincident (VGS Angle 3.75/TCH 37).	
					
		UNACO		PERGE	
				4 NM Holding Pattern	
					
		2200		2200	
		281°		101°	
		281°		6000	
		3.00°		2200	
		TCH 37			
		5.4 NM		6.3 NM	
CATEGORY		A		B	
LP MDA		1140-1 705 (800-1)		1140-2 705 (800-2)	
LNAV MDA		1140-1 705 (800-1)		1140-2 705 (800-2)	
CIRCLING		1180-1 745 (800-1)		1180-2¼ 745 (800-2¼)	
				1300-2¾ 865 (900-2¾)	