

WAAS CH 77930 W33A	APP CRS 331°	Rwy Idg TDZE 968 Apt Elev 968
--	------------------------	---

RNAV (GPS) RWY 33

HARRY STERN (BWP)


RNP APCH - GPS.


⚠

Circling NA to Rwy 3 and 21. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Rwy 33 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using FFM altimeter setting. When local altimeter setting not received, use FFM altimeter setting and increase LPA DA to 1290 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1322 feet and all visibilities ½ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climb to 3000 direct FAMMS and hold.

AWOS-3 127.875	MINNEAPOLIS CENTER 127.35 278.3	UNICOM 123.0 (CTAF)
--------------------------	---	-------------------------------



3000	FAMMS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 26).				
						
		CATEGORY	A	B	C	D
LPV DA		1218- ³ / ₄		250 (300- ³ / ₄)		
LNAV/ VNAV DA		1250- ⁷ / ₈		282 (300- ⁷ / ₈)		
LNAV MDA		1320-1		352 (400-1)		
CIRCLING		1520-1	552 (600-1)	1660-2 692 (700-2)	1660-2 ¹ / ₄ 692 (700-2 ¹ / ₄)	

