


WAAS CH 42502 W34A	APP CRS 343°	Rwy Idg 4601 TDZE 16 Apt Elev 16
--	------------------------	---

RNAV (GPS) RWY 34
EMMONAK (ENM) (PAEM)

A If local altimeter setting not received, use St Mary's altimeter setting and increase all DAs 168 feet and MDAs 180 feet. VDP NA with St Mary's altimeter setting. DME/DME RNP- 0.3 NA. Baro-VNAV NA when using St Mary's altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 48°C (119°F).

MISSED APPROACH: Climb to 1600 direct ECKIX and left turn via 253° track to ZEDET and left turn via 149° track to OFQIM and hold.

AWOS-3P 135.35	ANCHORAGE CENTER 124.0	CTAF 122.9 
--------------------------	----------------------------------	--



1600 ↑	ECKIX ✧	tr 253°	ZEDET ✧	tr 149°	OFQIM ✧	VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00/TCH 32).	
* LNAV only						OFQIM	4 NM Holding Pattern
RW34 0.9		KAVWI		1600 163° ← 343°		GP 3.00° TCH 35	
0.9		3.6 NM		6.5 NM			
CATEGORY	A		B		C		D
LPV DA			266-1		250 (300-1)		
LNAV/ VNAV DA			320-1		304 (400-1)		
LNAV MDA			320-1		304 (400-1)		
CIRCLING	520-1		504 (600-1)		520-1½ 504 (600-1½)		580-2 564 (600-2)

