

WAAS
CH **40440**
W01A

APP CRS
007°

Rwy Idg
TDZE **1276**
Apt Elev **1303**

RNAV (GPS) RWY 1

WILKES COUNTY (UKF)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hickory altimeter setting and increase LPV DA to 1566 feet and LNAV/VNAV DA to 1669 feet and LNAV/VNAV visibility all Cats ¼ SM. Increase all MDAs 100 feet and LNAV visibility Cats C/D ¼ SM and Circling Cat C ½ SM. For inop ALS when using Hickory altimeter setting, increase LPV all Cats visibility to 1 SM. VDP and Baro-VNAV NA when using Hickory altimeter setting.

MALSR

AS

MISSED APPROACH: Climb to 1800 then climbing right turn to 5000 direct HAPRI and hold, continue climb-in-hold to 5000.

AWOS-3 126.625	ATLANTA CENTER 125.15 263.0	UNICOM 122.7 (CTAF) 1
--------------------------	---------------------------------------	--

• 3730

Λ 2709 ±

30 NM to HAPRI

7100

15 NM to HAPRI

5000

097°

HAPRI

277°

30 NM to HAPRI (NoPT)

5000

097°

HAPRI

277°

1369 ±

RW01

JATLO

2.7 NM to RW01

2081 ±

(FAF)

IRIVE

2667 Λ

Λ 2798

007°

3600

(b)

(IF/IAF)

HAPRI

187°

007°

5 NM

Λ 2253

1470

5 NM Holding Pattern

HAPRI

IRIVE

JATLO

2.7 NM to RW01

1800

5000

HAPRI

5000

←187°

007°

007°

3600

*2160

RW01

*1 NM to RW01

*LNAV only.

GP 3.00°

TCH 59

6 NM

4.5 NM

1.7 NM

1 NM

CATEGORY	A	B	C	D
LPV DA	1476-½		200 (200-½)	
LNAV/VNAV DA	1579-⅝		303 (300-⅝)	
LNAV MDA	1620-½	344 (400-½)	1620-⅝	344 (400-⅝)
CIRCLING	1800-1 497 (500-1)	1880-1 577 (600-1)	1880-1½ 577 (600-1½)	2240-3 937 (1000-3)

ELEV 1303

TDZE 1276

61

6201 X 100

007°

1

REIL Rwy 19

MIRL Rwy 1-19

NORTH WILKESBORO, NORTH CAROLINA

Amtd 1 17AUG17

36°13'N-81°06'W

WILKES COUNTY (UKF)

RNAV (GPS) RWY 1