

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply.

ALSF-2

MISSED APPROACH: Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

ORLANDO APP CON 134.95 281.425	NASA TOWER ★ 128.55 (CTAF) 284.0	GND CON 121.75
-----------------------------------	-------------------------------------	-------------------

RADAR REQUIRED

MSA RW15 25 NM
3000

ROCIT (IF) 2500 (6) 1500 (6) 155°
STARS (FAF) 1500
RWY 15 105 ± A
R-2935, R-2934, R-2932, R-2933
CAPE CANAVERAL SFS SKID STRIP
ELEV 9, TDZE 8

ROCIT 2500

STARS 1500

RWY 15

GP 3.00° TCH 55

155°

1500

6.1 NM

3.6 NM

0.9 NM

800

2500

EARTH

*0.9 NM to RWY 15

*LNAV only

CATEGORY	A	B	C	D	E
LPV DA		208-1	200 (200-1)		
LNAV/VNAV DA		286-1	278 (300-1)		
LNAV MDA		360-1	352 (400-1)		
CIRCLING	420-1 411 (500-1)	460-1 451 (500-1)	940-2¾ 931 (1000-2¾)	940-3	931 (1000-3)

ELEV 9, TDZE 8

155°

TWR 107

1500' x 300'

HIRL Rwy 15-33

TITUSVILLE, FLORIDA

Amndt 1A 25MAY17

SPACE FLORIDA LAUNCH AND LANDING FACILITY (TTS)

28°37'N-80°42'W

RNAV (GPS) RWY 15