

LOC/DME I-XNA

111.55

APP CRS

159°

Rwy ldg

8800

TDZE

1287

Apt Elev

1288

Chan 52 (Y)

ILS or LOC RWY 16L

NORTHWEST ARKANSAS NTL (XNA)

DME required.

For inop ALS, increase S-ILS 16L Cat E visibility to RVR 4000 and S-LOC 16L Cats C, D, and E visibility to RVR 6000.

* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1800 then climbing left turn to 3400 on heading 133° and RZC VORTAC R-204 to LNSDY/RZC 10.3 DME and hold.

ATIS 119.425	RAZORBACK APP CON ★ 121.0 244.575	NORTHWEST ARKANSAS NTL TOWER ★ 127.1 (CTAF) 0	GND CON 121.9
-----------------	--------------------------------------	--	------------------

Diagram details: HUNTO (11) at 339°/159° with 5700/3400 ft altitudes. JADIR (5) at 3000 ft. SEYOD (2.3) at 1448 ft. MABDV (0.1) at 1539± ft. RAZORBACK (116.4 RZC) at 1855 ft. Localizer 111.55 (Chan 52 Y) at 1749 ft. Procedure NA for arrivals at RZC VORTAC on V140 eastbound. MSA RZC 25 NM with 3200, 3600, and 4500 ft altitudes. MISSED APCH FIX at 204°/024° with 116.4 RZC (Chan 111) and LNSDY RZC 10.3.

ELEV 1288

D

TDZE 1287

HIRL Rwy 16L-34R

MIRL Rwy 16R-34L

One Minute Holding Pattern

HUNTO I-XNA 11

JADIR I-XNA 5

SEYOD I-XNA 2.3

I-XNA DME ANTENNA

MABDV I-XNA 0.1

1800

3400

hdg 133°

RZC R-204

LNSDY RZC 10.3

5700

3400

339°

159°

159°

3000

2140

6 NM

2.7 NM

1.4 NM

0.9

0.2

GS 3.00°

TCH 57

CATEGORY	A	B	C	D	E
S-ILS 16L*	1487/24 200 (200-½)				
S-LOC 16L	1700/24 413 (500-½)		1700/40 413 (500-¾)		
CIRCLING	1740-1 452 (500-1)	1760-1 472 (500-1)	2040-2¼ 752 (800-2¼)	2080-2½ 792 (800-2½)	2080-2¾ 792 (800-2¾)

FAYETTEVILLE/SPRINGDALE/ROGERS, ARKANSAS

Orig 20APR23

36°17'N-94°18'W

NORTHWEST ARKANSAS NTL (XNA)

ILS or LOC RWY 16L