

RADAR INSTRUMENT APPROACH MINIMUMS

LEMOORE NAS (REEVES FIELD)(KNLC), Leemore, CA Amdt 8

19MAY22 (22139) (USN) ELEV 228

RADAR - (E) 125.95 270.8x 314.0x 317.575x 322.45x 323.15x 336.4x 346.375x 348.75x 353.55x
363.7x 370.875x 377.075x 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ¹⁴	32L ²⁶	3.0°/40/743	ABCDE	327-½	100	(100-¼)
	14L	3.0°/54/983	ABCDE	319-½	100	(100-½)
	14R ⁵	3.0°/52/977	ABCDE	328-½	100	(100-½)
	32R ⁵	3.0°/46/870	ABCDE	321-½	100	(100-½)
ASR ⁴	32L ³⁷		AB	580-½	353	(400-½)
			CDE	580-⅝	353	(400-⅝)
	14L		ABCDE	560-1	341	(400-1)
	14R ⁵		AB	680-1	452	(500-1)
			CDE	680-1⅓	452	(500-1⅓)
	32R ⁵		AB	760-1	539	(600-1)
			CDE	760-1½	539	(600-1½)
CIR ⁸	14L, 14R, 32L		AB	680-1	452	(500-1)
			C	700-1½	472	(500-1½)
			DE	780-2	552	(600-2)
	32R		AB	760-1	532	(600-1)
			C	760-1½	532	(600-1½)
			DE	780-2	552	(600-2)

¹No-NOTAM MP: PAR-Rwy 14R-32L 1600-2400Z++ Mon, Rwy 14L-32R 1600-2400Z++ Wed.

²When ALS inop, increase vis to ½ mile.

³When ALS inop, increase vis to 1 mile.

⁴Simultaneous approaches authorized.

⁵Pattern at 2800 ft.

⁶Caution: WCH group 4: 15 ft less than required 20 ft.

⁷Step Down Fix at 3 NM from thld, 1100 min.

⁸Circling authorized only from ASR.

15 MAY 2025 to 12 JUN 2025

15 MAY 2025 to 12 JUN 2025

RADAR INSTRUMENT APPROACH MINIMUMS