

WAAS CH 72817 W13A	APP CRS 133°	Rwy Idg 5720 TDZE 67 Apt Elev 70
--	------------------------	---

RNAV (GPS) RWY 13

BATON ROUGE METRO, RYAN FLD (BTR)


⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hammond altimeter setting and increase all DA 91 feet and all MDA 100 feet, and increase LNAV/VNAV all Cats visibility ¼ mile, and LNAV Cats C and D visibility ⅓ mile. For inop MALS when using Hammond altimeter setting, increase LPV all Cats visibility to ⅓ mile, LNAV Cat C and D visibility to 1⅓ mile. Baro-VNAV and VDP NA when using Hammond altimeter setting.

MALS

MISSED APPROACH: Climb to 2300 direct FADAD and hold.

ATIS 125.2	BATON ROUGE APP CON ★ 120.3 278.3	RYAN TOWER ★ 118.45 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 119.4	UNICOM 122.95
----------------------	---	--	-------------------------	--------------------------	-------------------------



BOYAG				
2000				
133°				
DUNAY				
1400				
*1.3 NM to RWY13				
*LNAV only.				
RWY13				
GP 3.00° TCH 57				
6 NM 2.7 NM 1.3				
CATEGORY	A	B	C	D
LPV DA	267-½		200 (200-½)	
LNAV/VNAV DA	465-⅞		398 (400-⅞)	
LNAV MDA	540-½		540-1 473 (500-1)	
CIRCLING	560-1 490 (500-1)		780-2 770 (800-2)	
	660-1 590 (600-1)		840-2½ 770 (800-2½)	

