

ILS or LOC RWY 23

LOC I-POB 110.9	APCH CRS 228°	Rwy ldg TDZE Arprt Elev 7501 200 225	[USAF]	POPE AAF (KPOB)
---------------------------	-------------------------	--	--------	-----------------

RADAR required

▼ *When ALS inop, increase RVR to 40 and vis to ¾ mile.
 ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile;
 CAT CD RVR to 60, vis to 1½ miles.
 *** Circling not authorized SE of Rwy 5-23.
 **** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile;
 CAT CD vis to 1½ miles.

ATIS
132.3 353.725

FAYETTEVILLE APP CON
125.175 285.575 (271° - 090°)
133.0 290.25 (091° - 270°)

TOWER
135.025 291.1

GND CON
124.55 275.8

CLNC DEL
124.55 275.8

CAUTION: Avoid R-5311 A, B, C
 located 2.5 DME West of field

EMERG SAFE ALT 100 NM 5300

2000	AWGUS POB 12	KECCN POB 3.7	NAYIN POB 4.8 RADAR	ACENO POB 12	POB 17
------	-----------------	------------------	---------------------------	-----------------	--------

ELEV	225	TDZE	200
------	-----	------	-----

Rwy 5 ldg 7501'
 Rwy 23 ldg 7501'

CATEGORY	A	B	C	D
S-ILS 23 *	400/24		200 (200-½)	
S-LOC 23 **	620/24 420 (500-½)		620/40 420 (500-¾)	
*** C CIRCLING	760-1 542 (600-1)		920-2 702 (800-2) 1060-2 842 (900-2¾)	
WITHOUT LAST STEPDOWN FIX				
S-LOC 23 ****	640/24 440 (500-½)		640/45 440 (500-¾)	

FAF to MAP 3.2 NM

Knots	60	90	120	150	180
Min:Sec	3:12	2:08	1:36	1:17	1:01

SE-2, 12 JUN 2025 to 10 JUL 2025

SE-2. 12 JUN 2025 to 10 JUL 2025