



WAAS CH 86417 W14A	APP CRS 141°	Rwy Idg TDZE Apt Elev	8001 802 815
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 14
FORT WAYNE INTL (FWA)

ASR	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.		MISSED APPROACH: Climb to 3000 direct CABAC and hold.	
	ATIS 121.25 360.825	FORT WAYNE APP CON 127.2 284.6	FORT WAYNE TOWER 119.1 269.325	GND CON 121.9 348.6



4 NM Holding Pattern		LABIC	MUPUE	3000	CABAC
3000		321°	141°	141°	
GP 3.00°		TCH 53			
		2500	2500	2500	
		6.1 NM	3.6 NM	1.5 NM	
CATEGORY	A	B	C	D	
LPV DA		1002-3/4	200 (200-3/4)		
LNAV/VNAV DA		1199-1 1/4	397 (400-1 1/4)		
LNAV MDA	1320-1	518 (600-1)	1320-1 3/8	518 (600-1 3/8)	
CIRCLING	1320-1	505 (600-1)	1420-1 3/4	1520-2 1/4	
			605 (700-1 3/4)	705 (800-2 1/4)	