



WAAS CH 82417 W32A	APP CRS 321°	Rwy Idg TDZE Apt Elev	8001 800 815
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32

FORT WAYNE INTL (FWA)

⚠ ASR For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. ** RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR AS MISSED APPROACH: Climb to 3000 direct LABIC and hold.			
ATIS 121.25 360.825	FORT WAYNE APP CON 127.2 284.6	FORT WAYNE TOWER 119.1 269.325	GND CON 121.9 348.6	CLNC DEL 124.75



3000

↑

LABIC

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 76).

DABYA

2300

CABAC

4 NM Holding Pattern

*LNAV only

RW32

1.3

3.2 NM

6 NM

*1.3 NM to RW32

2300

141°

321°

3000

GP 3.00°

TCH 56

CATEGORY	A	B	C	D
LPV DA	**1000/24 200 (200-½)			
LNAV/VNAV DA	1250/50 450 (500-1)			
LNAV MDA	1280/24 480 (500-½)	1280/50 480 (500-1)		
CIRCLING	1300-1 485 (500-1)	1420-1¾ 605 (700-1¾)	1520-2¼ 705 (800-2¼)	