

WAAS CH 77638 W31A	APP CRS 313°	Rwy Ldg 2821 TDZE 836 Apt Elev 836
--	------------------------	---

RNAV (GPS) RWY 31
SMITH FLD (SMD)

 NA  -22°C	Rwy 31 helicopter visibility reduction below 1 SM NA. DME/DME RNP-0.3 NA. Procedure NA at night. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase all MDA 40 feet, LP Cat C visibility ¼ SM and LNAV Cat C visibility ½ SM.	MISSED APPROACH: Climb to 2700 direct GRUSS and on track 273° to WERBU and hold.
---	---	--

AWOS-3

124.55

FORT WAYNE APP CON

127.2 284.6

UNICOM

122.8 (CTAF) **L**

MISSED APCH FIX

Procedure NA for arrivals at TWERP on V8 eastbound and V422 eastbound.

FORT WAYNE

Procedure NA for arrival on FWA VORTAC
airway radials 022 CW 174.

ELEV 836

TDZE 836

MIRI Rwsys.5-23 and 13-31 0

Amdt 1A 25MAY17

41°09'N-85°09'W

SMITH FLD (SMD)

RNAV (GPS) RWY 31

EC-2, 12 JUN 2025 to 10 JUL 2025

EC-2, 12 JUN 2025 to 10 JUL 2025